

LEKTRA-LIFT™

HITCH CARRIERS

**MAKING IT EASY,
SAFE & VERSATILE.**

MOBILITY SCOOTER LIFT

PATENT PENDING



Allows door/gate access
when down



5 ft. removable ramps
can be used anywhere



Automatically folds up
behind your vehicle

**SEE IT IN ACTION AT
www.lektra-lift.com**



**REMOTE
CONTROL**

BEST FEATURES IN THE INDUSTRY!

- Easy Installation and Quick Transfer Between Cars, Trucks, SUVs and Motor Homes
- For Use With Class II, Class III, Class IV or Class V Hitch*
- Battery Operated or Optional Direct Wire Operation
- Up To 500 lbs. Maximum Load**
- Light Bar For Extra Visibility
- Other Ramp Styles And Accessories Available For A Variety of Applications

*Check Towing Capacity in Your Vehicle Owner's Manual .
**With Class IV And Class V Hitch.

Razor Products, Inc.
7808 U.S. Hwy 30 W
Fort Wayne, IN 46818

866-574-LIFT (5438)

made in the U.S.A.



**MAKING IT EASY,
SAFE & VERSATILE.**

The Lektra-Lift Hitch Carrier System is the most versatile receiver mounted lift available. There are a variety of optional accessories that can be used with the Lektra-Lift.



This allows you to transport Mobility Scooters, ATVs, Lawn Tractors, Mopeds, Dirt and Sport Bikes, and can also be used for moving other large items that won't easily fit inside your vehicle.

Ask your dealer or call us to discuss the accessories that fit your needs.

866-574-LIFT (5438)



LIFT SYSTEM DIMENSIONS

FULLY ASSEMBLED

Total Weight: 106 lbs. (not including battery)
Overall Length: 52 in.
Overall Width: (including Bi-Fold Platform): 60 in.
Overall Height: 37 in.

POWER HEAD

Total Weight: 52 lbs. (not including battery)
Length: 17 in.
Width: 21 in.
Height: 37 in.

**SUPPORT ASSEMBLY
WITH LICENSE PLATE HOLDER**

Total Weight: 27 lbs.
Length: 34 in.
Width: 23.5 in.
Height: 9.5 in.

BI-FOLD PLATFORM

Total Weight: 27 lbs.
DEPLOYED
Overall Length: 60 in. (platform surface: 51 in.)
Overall Width: 29.25 in. (platform surface: 29 in.)
Overall Height: 3 in.

FOLDED

Length: 60 in.
Width: 15 in.
Height: 5 in.

Maximum Lift Capacity: 500 lbs.
Maximum Lift Travel: 22 in.
Motor: 12-volt DC
Battery: 12-volt 18AH
Charger: 110-volt, 2amp trickle charge, off-board

